

Kolano 45° - krótkie

PE 100



d	S		I min	Z	Stp.	€/szt.	
	SDR 17.6	SDR 11				SDR 17.6	SDR 11
25		2.3	16	25	5		1,63
32		3.0	16	32	5		1,79
40		3.7	16	40	5		2,21
50	3,0	4.6	16	40	5		2,73
63	3,8	5.8	21	48	5		3,89
75	4.5	6.9	25	75	2	5,15	5,25
90	5.4	8.2	30	68	2	6,51	7,35
110	6.6	10.0	38	83	2	13,65	13,86
140	8.3	12.8	49	105	1	24,89	26,15
160	9.5	14.6	56	120	1	27,41	31,71
180	10.7	16.4	63	135	1	33,81	37,59
200	11.9	18.2	70	150	1	42,00	55,97
225	13.4	20.5	79	169	1	51,98	66,99

Trójnik 90° - długi

PE 100



d	S		I	Z	Stp.	€/szt.	
	SDR 17.6	SDR 11				SDR 17.6	SDR 11
25		2.3	41	62	5		2,90
32		3.0	51	75	5		3,50
40		3.7	55	82	5		4,20
50		4.6	51	83	5		5,50
63	3,8	5.8	70	114	5	7,90	7,60
75	4.5	6.9	73	120	2	9,90	11,40
90	5.4	8.2	86	153	2	14,95	17,60
110	6.6	10.0	95	168	2	21,30	25,00
125	7.4	11.4	100	177	1	30,00	35,30
140	8.3	12.8	105	193	1	45,60	53,30
160	9.5	14.6	124	225	1	52,85	61,90
180	10.7	16.4	119	233	1	74,40	87,50
200	11.9	18.2	127	251	1	106,40	126,00
225	13.4	20.5	138	272	1	126,70	149,20
250	14.2	22.8	148	314	1	153,00	211,90
280	15.9	25.5	160	346	1	262,30	308,60
315	17.9	28.7	170	380	1	335,50	457,04

Trójnik redukcyjny 90° - krótki

PE 100



d-d1-d	SDR 17/17.6		SDR 11		I min	€/szt.	
	S	S1	S	S1		SDR 17/17.6	SDR 11
110-63-110	6.6	5.8	10.0	5.8	48	18,38	28,67
110-90-110	6.6	5.1	10.0	8.2	48	18,48	29,30
160-110-160	9.5	6.3	14.6	10.0	56	55,65	61,53
225-110-225	13.4	6.3	20.5	10.0	89	105,11	131,78
225-125-225	13.4	7.1	20.5	11.4	79	106,89	133,25
225-160-225	13.4	9.1	20.5	14.6	89	107,94	134,82

